

1 in 20 (max)

1500

500

Landing every 500mm rise

2100

1000

Access ramp to fully comply with AD.M

- 11mm OSB Board
- 12.5mm Soundblock board
- 12.5mm Soundblock board,
- 146mm Jumbo Stud with Acoustic Matt insulation
- 12.5mm Soundblock board
- 12.5mm Soundblock board
- 11mm OSB Board

Status:	FEASIBILITY
----------------	-------------

Project: Proposed Scaffold Training Centre
--

Client:
UWTSD

Title: Proposed Ground Floor GA Plan
--

Scale: 1:100	Drawn by: BM
------------------------	------------------------

This drawing is the copyright of TRJ and may not be copied, altered, reproduced or passed to a third party without their consent.
Dimensions must be checked and verified on site, discrepancies should be reported.
THIS DRAWING SHOULD NOT BE SCALED



T. Richard Jones (BETWS) LTD
Foundry Road, Ammanford,
Carmarthenshire, SA18 2LS.
Tel: 01269 591103 Fax: 01269 596207
Email: enquiries@trijltd.co.uk

- 12mm Fibre board
- 12.5mm Plasterboard,
- 145mm Metal stud with insulation between
- 12.5mm Plasterboard
- 12mm Cement board

- 12.5mm Plasterboard
- GTEC CS70 RX C Studs
- 25mm Glass mineral wool insulation between studs
- 12.5mm Plasterboard

- 12.5mm Plasterboard
- GTEC CS70 RX C Studs
- 75mm Rockwool Insulation between studs
- 40mm Rockwool Insulation
- Existing structure

- Kingspan Kooltherm K118 Insulated 50mm + 12.5mm Plasterboard on Dabs
- 100mm Dense Concrete Block

- 100mm Concrete Block