



COLOURS

Rectangular

standard paving blocks

DEPTHS



50 | 80
Millimetres

FINISH

Sm

Smooth



200 x
100mm

AG Paving Blocks

Rectangular
colours

COLOURS



CREAGH PEAT BRINDLE



CRIEVE MIX



FOREST BLEND



OLDE GOLD



SILVER



SLATE



Frost
Resistant



Pedestrian
Use



Light
Traffic



Heavy
Traffic
80mm only



Trolley
Friendly



Abrasion
Resistant



Available in
permeable
(Xflo)



Machine
Lay available



T 028 8778 4208 | GB Sales T 0121 747 0202 | E specifications@ag.uk.com

AG.UK.COM



Rectangular

standard paving blocks

DEPTHS

50 | 80
Millimetres

FINISH

Sm
Smooth200 x
100mm

STANDARDS + PERFORMANCE

Product Type	Standard paving blocks
Manufactured to	BS EN 1338:2003
Surface Layer Efflorescence	Durable and hard wearing with a minimum surface layer of 4mm. State-of-the-art factory controlled vapour curing significantly reduces this naturally occurring chemical reaction
Tensile Splitting Strength	>3.6Mpa. This pressure applies to all sizes and depths. For specific force performance on a given size or depth please contact our Technical Specification Department
Installed to NBS Plus	BS 7533-4:2006 Q24 110

SUSTAINABILITY

Energy Use	100% renewable
Water Used	90% recycled water
Recyclable	100% of this product can be recycled
Manufacturing	Produced in the UK using responsibly sourced materials
Non-Primary Materials	61 – 70% (surface layer)
Waste Wood + Plastic	100% recycled
Carbon Footprint	We have a new state-of-the-art washing plant which enables AG to produce paving from 100% recycled waste aggregate. Please contact our Technical Specification Department if you are interested in specifying such a product
BREEAM	50: A Rating – according to the Green Guide to Specification 4th edition 2009. A+ Rating can be achieved when used in conjunction with a prepared recycled sub-base. 80mm: B Rating – according to the Green Guide to Specification 4th edition 2009. A Rating can be achieved when used in conjunction with a prepared recycled sub-base.

AG RECOMMENDATIONS

Close Jointing

AG recommends a close joint of between 2mm - 5mm as per BS 7533 to cater for product alignment (butt jointing should be avoided).

Jointing Sand

AG recommends that silver and slate coloured products are jointed with AG's Granite Sand.

Colour blending

AG recommends that products are blended from 3 packs from alternate sides using full vertical sections.

Please contact our Technical Specification Department for further details.


ADVICE + GUIDANCE

For advice and guidance on ordering, installation, good site practice, etc. visit our website:
professional.ag.uk.com/advice+guidance


For maintenance guidance and health and safety advice visit our website:
professional.ag.uk.com/maintenance

EDGES

Rectangular Supplied with standard straight angle chamfer. Xflo supplied with a medium to large radius round chamfer.



Straight Chamfer

Medium to Large Radius Round Chamfer
(Xflo 200x100x80mm only)

SPACER NIBS

50mm / 60mm / 80mm: 1.5mm spacers on each paver leaving a 2mm minimum joint when laid.

Xflo®: 3.25mm x 2 spacers on each paver leaving a 7mm minimum joint when laid.

FINISHES

Closed smooth surface which contains a carefully selected blend of UV resistant colours and not less than 350kg/m³ of cement in the top layer, ensuring a durable, hardwearing surface finish.

Frost
ResistantPedestrian
UseLight
TrafficHeavy
Traffic
80mm onlyTrolley
FriendlyAbrasion
ResistantAvailable in
permeable
(Xflo)Machine
Lay available

SPECIFICATION REFERENCE: NBS PLUS: Q24 110 SLAB/BRICK/SETT/COBBLE PAVINGS BS EN: 1339:2003



Rectangular

standard paving blocks

DEPTHS


50 | 80
Millimetres

FINISH

Sm
Smooth

200 x
100mm

STOCK INFORMATION

Standard product depth	Size (mm)	In Stock	Available Colours	m ² per pack	Units per m ²	Units per pack	Unit weight (kg)	Weight per pack (t)	Packs per 8 wheeler	Packs per unit lorry
50mm	200 x 100	Yes	Creagh Peat Brindle / Crieve Mix / Forest Blend / Olde Gold / Slate	11.52	50	576	2.3	1.42	11	IRE 16 / GB 19
		MTO	Silver							
Rectangular Machine Lay available										
80mm	200 x 100	Yes	Crieve Mix / Silver / Slate	9.72	50	486	3.7	1.7	9	16
		MTO	Creagh Peat Brindle / Forest Blend / Olde Gold							
Xflo Rectangular Machine Lay available										
80mm	200 x 100	Yes	Crieve Mix / Silver / Slate	9.6	50	480	3.55	1.65	10	16
		MTO	Creagh Peat Brindle / Forest Blend / Olde Gold							

MTO: Made To Order (minimum order quantities: 250m² per colour / size. Orders below these quantities should be priced on application).

Information for a specific colour / depth is available on request from our Technical Specification Department.

Machine lay available on 80mm depths – please contact our Technical Specification Department for more information.


Frost
Resistant

Pedestrian
Use

Light
Traffic

Heavy
Traffic
80mm only

Trolley
Friendly

Abrasion
Resistant

Available in
permeable
(Xflo)

Machine
Lay available

MANUFACTURING

Rectangular is manufactured from locally sourced premium aggregates. Its colour blends are achieved by using the latest computerised mixing systems. A closed top surface (smooth finish) is achieved by using the latest face mix manufacturing methods. PLANT OF MANUFACTURE (POM): **50mm:** Made at our Fivemiletown production plant. **80mm:** Made at our Toome production plant.

CERTIFICATION

ISO 9001
ISO 14001
ISO 45001
CE Marking

Quality Management.
Environmental Management.
Occupational Health and Safety Management.
Download our Declaration of Performance (DOP) data at: www.ag.uk.com/cemarking

