

Window Sampling Hole Journal

Inspection Pit Dimensions						Hand Vane: Raw Data						
Equipment or Rig Type Dando Terrier						Type	Geonor	Pilcon	Impact			
						16	19	19				
						Size (mm)	20	33	33			
Window Sampling: Tube Driving Data						25	Tick one box					
Tube dia	Depth		Recovery	Time	Casing depth	Depth	Peak			Remoulded		
(mm)	From	To	(m)	(min:sec)	(windowless)		1	2	3	1	2	3
102	GL	1.00	1.00									
102	1.00	2.00	0.70									
87	2.00	3.00	0.70									
87	3.00	3.60	0.50									
						Pocket Penetrometer: Raw Data						
						Depth	1	2	3	4	5	6
All depths are m below ground level						Use GDMS data entry to input raw data to HoleBASE						
Samples			Strata				Installation Details					
Type	No.	Depth	Depth	Description								
E/S 1.80-2.00		GL	0.65	MADE GROUND: Multicoloured silty sandy angular to subangular fine to coarse GRAVEL of brick, slag sandstone and limestone.								
		0.65	1.00	MADE GROUND: Black silty angular fine to medium GRAVEL of coke and coal.								
		1.00	1.40	No Recovery								
		1.40	1.60	MADE GROUND: Black silty angular fine to medium GRAVEL of coke and coal.								
		1.60	2.00	MADE GROUND: Multicoloured clayey subangular to subrounded fine to coarse GRAVEL of brick, coke, coal, limestone and sandstone. Fragments of wood and ceramics.								
		2.00	2.30	No Recovery								
		2.30	2.70	Soft grey CLAY. Possible TIDAL FLATS DEPOSITS								
		2.70	3.00	Fibrous brown PEAT.								
		3.00	3.60	Soft light and dark grey gravelly CLAY. Gravel is angular to subangular fine to coarse of sandstone. Possible weathered bedrock.								
				End of Hole			Backfill Details (if no installation)					
Key to soil samples: B = bulk D = tub L = liner ES = environmental soil												
Groundwater Strike		If Yes		Project			Project No					
0.90		Depth of strike	After 20 mins	Depth sealed	Briton Ferry			2012				
Remarks					Operator APEX		Date 09/03/2020		Hole No.			
					Logger PL		Date 09/03/2020		WS02			