

Window Sampling Hole Journal

Inspection Pit Dimensions						Hand Vane: Raw Data						
Equipment or Rig Type Dando Terrier						Type	Geonor	Pilcon	Impact			
						16	19	19				
						Size (mm)	20	33	33			
Window Sampling: Tube Driving Data						25	Tick one box					
Tube dia (mm)	Depth		Recovery (m)	Time (min:sec)	Casing depth (windowless)	Depth	Peak			Remoulded		
	From	To					1	2	3	1	2	3
102	GL	1.00	1.00									
102	1.00	2.00	0.90									
87	2.00	3.00	0.80									
87	3.00	4.00	0.40									
						Pocket Penetrometer: Raw Data						
						Depth	1	2	3	4	5	6
All depths are m below ground level						Use GDMS data entry to input raw data to HoleBASE						
Samples			Strata				Installation Details					
Type	No.	Depth	Depth	Description								
E/S 0.50-0.70		GL	1.60	MADE GROUND: Multicoloured slightly silty sandy angular to subangular fine to coarse GRAVEL of coke,coal,slag,limestone and sandstone. Fill.								
		1.60	2.20	MADE GROUND:Soft brown orange and grey clayey sandy subangular to subrounded fine to coarse GRAVEL of limestone, sandstone, brick and slag.								
		2.20	2.65	Soft dark grey and brown slightly sandy CLAY. Possible TIDAL FLAT DEPOSITS.								
		2.65	3.00	Fibrous brown PEAT. Possible TIDAL FLAT DEPOSITS.								
		3.00	3.50	Soft light grey gravelly CLAY. Gravel is angular to subangular fine to coarse of sandstone. Possible weathered bedrock. BRITHDIR MEMBER								
				End of Hole								
						Backfill Details (if no installation)						
Key to soil samples: B = bulk D = tub L = liner ES = environmental soil												
Groundwater Strike		If Yes		Project			Project No					
1.0m		Depth of strike	After 20 mins	Depth sealed	Briton Ferry			2012				
Remarks				Operator APEX		Date 09/03/2020		Hole No.				
				Logger PL		Date 09/03/2020						
								WS03				