

Window Sampling Hole Journal

Inspection Pit Dimensions						Hand Vane: Raw Data						
Equipment or Rig Type Dando Terrier						Type	Geonor	Pilcon	Impact			
						16	19	19				
						Size (mm)	20	33	33			
Window Sampling: Tube Driving Data						25 ☐ Tick one box						
Tube dia	Depth		Recovery	Time	Casing depth	Depth	Peak			Remoulded		
(mm)	From	To	(m)	(min:sec)	(windowless)		1	2	3	1	2	3
102	GL	1.00	1.00									
102	1.00	2.00	1.00									
87	2.00	3.00	0.80									
87	3.00	3.40	0.30									
						Pocket Penetrometer: Raw Data						
						Depth	1	2	3	4	5	6
All depths are m below ground level						Use GDMS data entry to input raw data to HoleBASE						
Samples			Strata				Installation Details					
Type	No.	Depth	Depth	Description								
E/S		GL	0.50	MADE GROUND: Black and orange angular fine to medium GRAVEL of coke, coal and brick.								
2.00-2.40		0.50	0.80	MADE GROUND: Soft brown slightly sandy slightly gravelly CLAY. Gravel is angular to subangular fine to coarse of sandstone, limestone coke and coal.								
		0.80	1.50	MADE GROUND: Multicoloured slightly silty sandy angular to subangular fine to coarse GRAVEL of limestone, brick, coke and slag.								
		1.50	2.40	Soft grey and brown peaty CLAY. Possible TIDAL FLATS DEPOSITS.								
		2.40	2.80	Fibrous brown PEAT.								
		2.80	3.40	Soft light grey slightly sandy gravelly CLAY. Gravel is angular to subangular fine to coarse of sandstone. Possible weathered bedrock.								
				End of Hole								
						Backfill Details (if no installation)						
Key to soil samples: B = bulk D = tub L = liner ES = environmental soil												
Groundwater Strike		If Yes		Project			Project No					
0.90		Depth of strike	After 20 mins	Depth sealed	Briton Ferry			2012				
Remarks Installation:				Operator APEX		Date 09/03/2020		Hole No.				
GL - 1.0m 50mm plain pipe				Logger PL		Date 09/03/2020		WS04				
1.0m - 3.40m 50mm slotted pipe												