

Window Sampling Hole Journal

Inspection Pit Dimensions						Hand Vane: Raw Data								
Equipment or Rig Type Dando Terrier						Type	Geonor	Pilcon	Impact					
						16		19		19				
						Size (mm)	20		33		33			
Window Sampling: Tube Driving Data						25		Tick one box						
Tube dia	Depth		Recovery	Time	Casing depth	Depth	Peak			Remoulded				
(mm)	From	To	(m)	(min:sec)	(windowless)		1	2	3	1	2	3		
102	GL	1.00	0.90											
87	1.00	2.00	0.60											
						Pocket Penetrometer: Raw Data								
						Depth	1	2	3	4	5	6		
All depths are m below ground level						Use GDMS data entry to input raw data to HoleBASE								
Samples			Strata						Installation Details					
Type	No.	Depth	Depth	Description										
E/S		GL	1.80	MADE GROUND: Multicoloured slightly silty sandy angular to subangular fine to coarse GRAVEL of coke,coal,slag,limestone and sandstone. Fill.										
0.50-0.70		1.80	2.00	MADE GROUNDBlack silty subangular to subrounded fine to coarse GRAVEL of fused slag										
				End of Hole										
									Backfill Details (if no installation)					
Key to soil samples: B = bulk D = tub L = liner ES = environmental soil														
Groundwater Strike		If Yes			Project						Project No			
0.90		Depth of strike	After 20 mins	Depth sealed	Briton Ferry						2012			
Remarks					Operator		APEX		Date		09/03/2020		Hole No.	
					Logger		PL		Date		09/03/2020		WS06	