

Window Sampling Hole Journal

Inspection Pit Dimensions						Hand Vane: Raw Data						
Equipment or Rig Type Dando Terrier						Type	Geonor	Pilcon	Impact			
						Size (mm)	16	19	19			
						20	33	33				
Window Sampling: Tube Driving Data						25 ☐ Tick one box						
Tube dia	Depth		Recovery	Time	Casing depth	Depth	Peak			Remoulded		
(mm)	From	To	(m)	(min:sec)	(windowless)		1	2	3	1	2	3
102	GL	1.00	1.00									
102	1.00	2.00	0.70									
87	2.00	3.00	NR									
87	3.00	3.60	0.50									
						Pocket Penetrometer: Raw Data						
						Depth	1	2	3	4	5	6
All depths are m below ground level						Use GDMS data entry to input raw data to HoleBASE						
Samples			Strata				Installation Details					
Type	No.	Depth	Depth	Description								
E/S 0.10-0.30 3x60mm glass jars		GL	0.30	MADE GROUND: Dark brown slightly gravelly silty fine to medium SAND. Gravel is angular to sub-angular fine to coarse of limestone and sandstone.								
		0.30	1.40	MADE GROUND: Multicoloured slightly silty sandy angular to subangular fine to coarse GRAVEL of coke,coal,slag,limestone and sandstone. Fragments of ceramics.								
		1.40	1.75	Soft to firm dark grey slightly sandy CLAY. Possible TIDAL FLAT DEPOSITS								
		1.75	2.00	Fibrous brown PEAT.								
		2.00	3.00	No Recovery								
		3.00	3.50	Soft to firm light grey gravelly CLAY. Gravel is angular to subangular fine to coarse sandstone. Possible weathered bedrock.								
				End of Hole								
							Backfill Details (if no installation)					
Key to soil samples: B = bulk D = tub L = liner ES = environmental soil												
Groundwater Strike		If Yes			Project			Project No				
1.00		Depth of strike	After 20 mins	Depth sealed	Briton Ferry			2012				
Remarks Installation:					Operator APEX		Date 09/03/2020		Hole No.			
GL - 1.50m 50mm plain pipe					Logger PL		Date 09/03/2020		WS10			
1.50m - 3.50m 50mm slotted pipe												