



Apex Testing Solutions Limited
Sturmi Way
Village Farm Industrial Estate
Pyle
Bridgend
CF33 6BZ

Attention: Laura Davies

Unit 7-8 Hawarden Business Park
Manor Road (off Manor Lane)
Hawarden
Deeside
CH5 3US
Tel: (01244) 528700
Fax: (01244) 528701
email: hawardencustomerservices@alsglobal.com
Website: www.alsenvironmental.co.uk

CERTIFICATE OF ANALYSIS

Date of report Generation:	21 July 2020
Customer:	Apex Testing Solutions Limited
Sample Delivery Group (SDG):	200714-71
Your Reference:	D20210
Location:	TATA - I H
Report No:	559905

We received 2 samples on Tuesday July 14, 2020 and 2 of these samples were scheduled for analysis which was completed on Tuesday July 21, 2020. Accredited laboratory tests are defined within the report, but opinions, interpretations and on-site data expressed herein are outside the scope of ISO 17025 accreditation.

Should this report require incorporation into client reports, it must be used in its entirety and not simply with the data sections alone.

Chemical testing (unless subcontracted) performed at ALS Life Sciences Ltd Hawarden (Method codes TM) or ALS Life Sciences Ltd Aberdeen (Method codes S).

All sample data is provided by the customer. The reported results relate to the sample supplied, and on the basis that this data is correct.

Incorrect sampling dates and/or sample information will affect the validity of results.

The customer is not permitted to reproduce this report except in full without the approval of the laboratory.

Approved By:

Sonia McWhan

Operations Manager





CERTIFICATE OF ANALYSIS

Validated

SDG: 200714-71
Location: TATA - I H

Client Reference: D20210
Order Number: 1286

Report Number: 559905
Superseded Report:

Received Sample Overview

Lab Sample No(s)	Customer Sample Ref.	AGS Ref.	Depth (m)	Sampled Date
22471875	BH1		1.00 - 2.00	13/07/2020
22471874	BH1		3.00 - 3.45	13/07/2020

Maximum Sample/Coolbox Temperature (°C) :

10.4

ISO5667-3 Water quality - Sampling - Part3 -

During Transportation samples shall be stored in a cooling device capable of maintaining a temperature of (5±3)°C.

ALS have data which show that a cool box with 4 frozen icepacks is capable of maintaining pre-chilled samples at a temperature of (5±3)°C for a period of up to 24hrs.

Only received samples which have had analysis scheduled will be shown on the following pages.



CERTIFICATE OF ANALYSIS

Validated

SDG: 200714-71
Location: TATA - I H

Client Reference: D20210
Order Number: 1286

Report Number: 559905
Superseded Report:

Results Legend

- X** Test
N No Determination Possible

Sample Types -

S - Soil/Solid
UNS - Unspecified Solid
GW - Ground Water
SW - Surface Water
LE - Land Leachate
PL - Prepared Leachate
PR - Process Water
SA - Saline Water
TE - Trade Effluent
TS - Treated Sewage
US - Untreated Sewage
RE - Recreational Water
DW - Drinking Water Non-regulatory
UNL - Unspecified Liquid
SL - Sludge
G - Gas
OTH - Other

Results Legend	Lab Sample No(s)		22471875		22471874	
	Customer Sample Reference		BH1		BH1	
	AGS Reference					
	Depth (m)		1.00 - 2.00		3.00 - 3.45	
	Container		1kg Cardboard Container	250g Amber Jar (ALE210)	60g VOC (ALE215)	1kg Cardboard Container
	Sample Type		S	S	S	S
Alkali Metals by iCap-OES (Soil)	All	NDPs: 0 Tests: 2		X		X
Asbestos ID in Solid Samples	All	NDPs: 0 Tests: 2	X		X	
EPH CWG GC (S)	All	NDPs: 0 Tests: 2		X		X
GRO by GC-FID (S)	All	NDPs: 0 Tests: 2			X	X
Metals in solid samples by OES	All	NDPs: 0 Tests: 2		X		X
PAH by GCMS	All	NDPs: 0 Tests: 2		X		X
pH	All	NDPs: 0 Tests: 2		X		X
Sample description	All	NDPs: 0 Tests: 2		X		X
Total Organic Carbon	All	NDPs: 0 Tests: 2		X		X
TPH CWG GC (S)	All	NDPs: 0 Tests: 2		X		X
VOC MS (S)	All	NDPs: 0 Tests: 2			X	X



CERTIFICATE OF ANALYSIS

Validated

SDG: 200714-71
Location: TATA - I H

Client Reference: D20210
Order Number: 1286

Report Number: 559905
Superseded Report:

Sample Descriptions

Grain Sizes

very fine	<0.063mm	fine	0.063mm - 0.1mm	medium	0.1mm - 2mm	coarse	2mm - 10mm	very coarse	>10mm
------------------	----------	-------------	-----------------	---------------	-------------	---------------	------------	--------------------	-------

Lab Sample No(s)	Customer Sample Ref.	Depth (m)	Colour	Description	Inclusions	Inclusions 2
22471874	BH1	3.00 - 3.45	Dark Brown	Sand	Vegetation	Stones
22471875	BH1	1.00 - 2.00	Dark Brown	Loamy Sand	Vegetation	Stones

These descriptions are only intended to act as a cross check if sample identities are questioned, and to provide a log of sample matrices with respect to MCERTS validation. They are not intended as full geological descriptions.

We are accredited to MCERTS for sand, clay and loam/topsoil, or any of these materials - whether these are derived from naturally occurring soil profiles, or from fill/made ground, as long as these materials constitute the major part of the sample.

Other coarse granular materials such as concrete, gravel and brick are not accredited if they comprise the major part of the sample.



CERTIFICATE OF ANALYSIS

Validated

SDG: 200714-71
Location: TATA - I HClient Reference: D20210
Order Number: 1286Report Number: 559905
Superseded Report:

PAH by GCMS

Results Legend			Customer Sample Ref.	BH1	BH1			
#	ISO17025 accredited.		Depth (m) Sample Type Date Sampled Sample Time Date Received SDG Ref Lab Sample No.(s) AGS Reference	1.00 - 2.00	3.00 - 3.45			
M	mCERTS accredited.			Soil/Solid (S)	Soil/Solid (S)			
aq	Aqueous / settled sample.							
diss.filt	Dissolved / filtered sample.							
tot.unfilt	Total / unfiltered sample.							
*	Subcontracted - refer to subcontractor report for accreditation status.							
**	% recovery of the surrogate standard to check the efficiency of the method. The results of individual compounds within samples aren't corrected for the recovery							
(F)	Trigger breach confirmed							
1-3*5@	Sample deviation (see appendix)							
Component	LOD/Units	Method						
Naphthalene-d8 % recovery**	%	TM218	91.8	92.1				
Acenaphthene-d10 % recovery**	%	TM218	89.9	90.7				
Phenanthrene-d10 % recovery**	%	TM218	92.1	92.2				
Chrysene-d12 % recovery**	%	TM218	82.8	82.7				
Perylene-d12 % recovery**	%	TM218	80.4	80.7				
Naphthalene	<9 µg/kg	TM218	14.1	<9				
Acenaphthylene	<12 µg/kg	TM218	<12	<12				
Acenaphthene	<8 µg/kg	TM218	<8	<8				
Fluorene	<10 µg/kg	TM218	<10	<10				
Phenanthrene	<15 µg/kg	TM218	46.3	<15				
Anthracene	<16 µg/kg	TM218	<16	<16				
Fluoranthene	<17 µg/kg	TM218	49.6	<17				
Pyrene	<15 µg/kg	TM218	40.7	<15				
Benz(a)anthracene	<14 µg/kg	TM218	22.3	<14				
Chrysene	<10 µg/kg	TM218	28.5	<10				
Benzo(b)fluoranthene	<15 µg/kg	TM218	32.5	<15				
Benzo(k)fluoranthene	<14 µg/kg	TM218	<14	<14				
Benzo(a)pyrene	<15 µg/kg	TM218	<15	<15				
Indeno(1,2,3-cd)pyrene	<18 µg/kg	TM218	<18	<18				
Dibenzo(a,h)anthracene	<23 µg/kg	TM218	<23	<23				
Benzo(g,h,i)perylene	<24 µg/kg	TM218	<24	<24				
PAH, Total Detected USEPA 16	<118 µg/kg	TM218	234	<118				



CERTIFICATE OF ANALYSIS

Validated

SDG: 200714-71
Location: TATA - I HClient Reference: D20210
Order Number: 1286Report Number: 559905
Superseded Report:

TPH CWG (S)

Results Legend			Customer Sample Ref.		BH1		BH1					
#	ISO17025 accredited.	Depth (m) Sample Type Date Sampled Sample Time Date Received SDG Ref Lab Sample No.(s) AGS Reference	1.00 - 2.00 Soil/Solid (S) 13/07/2020 . 14/07/2020 200714-71 22471875	3.00 - 3.45 Soil/Solid (S) 13/07/2020 . 14/07/2020 200714-71 22471874								
M	mCERTS accredited.											
aq	Aqueous / settled sample.											
diss.filt	Dissolved / filtered sample.											
tot.unfilt	Total / unfiltered sample.											
*	Subcontracted - refer to subcontractor report for accreditation status.											
**	% recovery of the surrogate standard to check the efficiency of the method. The results of individual compounds within samples aren't corrected for the recovery											
(F)	Trigger breach confirmed											
1-3*5@	Sample deviation (see appendix)											
Component	LOD/Units											Method
GRO Surrogate % recovery**	%	TM089	87.2	107								
Aliphatics >C5-C6	<10 µg/kg	TM089	<10	<10								
Aliphatics >C6-C8	<10 µg/kg	TM089	13.6	<10								
Aliphatics >C8-C10	<10 µg/kg	TM089	19.8	<10								
Aliphatics >C10-C12	<1000 µg/kg	TM414	<1000	<1000								
Aliphatics >C12-C16	<1000 µg/kg	TM414	<1000	<1000								
Aliphatics >C16-C21	<1000 µg/kg	TM414	<1000	<1000								
Aliphatics >C21-C35	<1000 µg/kg	TM414	49200	20600								
Aliphatics >C35-C44	<1000 µg/kg	TM414	14500	5020								
Total Aliphatics >C10-C44	<5000 µg/kg	TM414	64500	25600								
Total Aliphatics & Aromatics >C10-C44	<10000 µg/kg	TM414	68700	28300								
Aromatics >EC5-EC7	<10 µg/kg	TM089	<10	<10								
Aromatics >EC7-EC8	<10 µg/kg	TM089	<10	<10								
Aromatics >EC8-EC10	<10 µg/kg	TM089	13.6	<10								
Aromatics > EC10-EC12	<1000 µg/kg	TM414	<1000	<1000								
Aromatics > EC12-EC16	<1000 µg/kg	TM414	<1000	<1000								
Aromatics > EC16-EC21	<1000 µg/kg	TM414	<1000	<1000								
Aromatics > EC21-EC35	<1000 µg/kg	TM414	2620	1520								
Aromatics >EC35-EC44	<1000 µg/kg	TM414	<1000	<1000								
Aromatics > EC40-EC44	<1000 µg/kg	TM414	<1000	<1000								
Total Aromatics > EC10-EC44	<5000 µg/kg	TM414	<5000	<5000								
Total Aliphatics & Aromatics >C5-C44	<10000 µg/kg	TM414	64500	25600								
Total Aliphatics >C5-C10	<50 µg/kg	TM089	<50	<50								
Total Aromatics >EC5-EC10	<50 µg/kg	TM089	<50	<50								
GRO >C5-C10	<20 µg/kg	TM089	<20	<20								



CERTIFICATE OF ANALYSIS

Validated

SDG: 200714-71
Location: TATA - I H

Client Reference: D20210
Order Number: 1286

Report Number: 559905
Superseded Report:

VOC MS (S)

Results Legend		Customer Sample Ref.	BH1		BH1				
#	ISO17025 accredited.								
M	mCERTS accredited.								
aq	Aqueous / settled sample.								
diss.filt	Dissolved / filtered sample.								
tot.unfilt	Total / unfiltered sample.								
*	Subcontracted - refer to subcontractor report for accreditation status.								
**	% recovery of the surrogate standard to check the efficiency of the method. The results of individual compounds within samples aren't corrected for the recovery								
(F)	Trigger breach confirmed								
1-3*5@	Sample deviation (see appendix)								
Component	LOD/Units	Method							
Dibromofluoromethane**	%	TM116	106		115				
Toluene-d8**	%	TM116	90.2		96.4				
4-Bromofluorobenzene**	%	TM116	72.9		97.1				
Methyl Tertiary Butyl Ether	<10 µg/kg	TM116	<10		<10				
			M		M				
Benzene	<9 µg/kg	TM116	<9		<9				
			M		M				
Toluene	<7 µg/kg	TM116	<7		<7				
			M		M				
Ethylbenzene	<4 µg/kg	TM116	<4		<4				
			M		M				
p/m-Xylene	<10 µg/kg	TM116	<10		<10				
			#		#				
o-Xylene	<10 µg/kg	TM116	<10		<10				
			M		M				
Sum of Detected Xylenes	<0.02 mg/kg	TM116	<0.02		<0.02				
Sum of BTEX	<40 µg/kg	TM116	<40		<40				
					</				



CERTIFICATE OF ANALYSIS

Validated

SDG: 200714-71 **Client Reference:** D20210 **Report Number:** 559905
Location: TATA - I H **Order Number:** 1286 **Superseded Report:**

Asbestos Identification - Solid Samples

Results Legend

ISO17025 accredited.
M mCERIS accredited.
* Subcontracted test.
(F) Trigger breach confirmed
1-5&*S@ Sample deviation (see appendix)

		Date of Analysis	Analysed By	Comments	Amosite (Brown) Asbestos	Chrysotile (White) Asbestos	Crocidolite (Blue) Asbestos	Fibrous Actinolite	Fibrous Anthophyllite	Fibrous Tremolite	Non-Asbestos Fibre
Cust. Sample Ref. Depth (m) Sample Type Date Sampled Date Received SDG Original Sample Method Number	BH1 1.00 - 2.00 SOLID 13/07/2020 00:00:00 14/07/2020 06:00:00 200714-71 22471875 TM048	20/07/2020	James Richards	-	Not Detected (#)	Not Detected (#)	Not Detected (#)	Not Detected (#)	Not Detected (#)	Not Detected (#)	Not Detected
Cust. Sample Ref. Depth (m) Sample Type Date Sampled Date Received SDG Original Sample Method Number	BH1 3.00 - 3.45 SOLID 13/07/2020 00:00:00 14/07/2020 06:00:00 200714-71 22471874 TM048	20/07/2020	Marcin Magdziarek	-	Not Detected (#)	Not Detected (#)	Not Detected (#)	Not Detected (#)	Not Detected (#)	Not Detected (#)	Not Detected



CERTIFICATE OF ANALYSIS

Validated

SDG: 200714-71 **Client Reference:** D20210 **Report Number:** 559905
Location: TATA - I H **Order Number:** 1286 **Superseded Report:**

Table of Results - Appendix

Method No	Reference	Description
PM024	Modified BS 1377	Soil preparation including homogenisation, moisture screens of soils for Asbestos Containing Material
TM048	HSG 248, Asbestos: The analysts' guide for sampling, analysis and clearance procedures	Identification of Asbestos in Bulk Material
TM089	Modified: US EPA Methods 8020 & 602	Determination of Gasoline Range Hydrocarbons (GRO) by Headspace GC-FID (C4-C12)
TM116	Modified: US EPA Method 8260, 8120, 8020, 624, 610 & 602	Determination of Volatile Organic Compounds by Headspace / GC-MS
TM132	In - house Method	ELTRA CS800 Operators Guide
TM133	BS 1377: Part 3 1990;BS 6068-2.5	Determination of pH in Soil and Water using the GLpH pH Meter
TM181	US EPA Method 6010B	Determination of Routine Metals in Soil by iCap 6500 Duo ICP-OES
TM218	Shaker extraction - EPA method 3546.	The determination of PAH in soil samples by GC-MS
TM224	US EPA Method 6010B	Determination of Alkaline Metals by iCap 6500 Duo ICP-OES
TM414	Analysis of Petroleum Hydrocarbons in Environmental Media – Total Petroleum Hydrocarbon Criteria	Determination of Speciated Extractable Petroleum Hydrocarbons in Soils by GCxGC-FID

NA = not applicable.

Chemical testing (unless subcontracted) performed at ALS Life Sciences Ltd Hawarden (Method codes TM) or ALS Life Sciences Ltd Aberdeen (Method codes S).



CERTIFICATE OF ANALYSIS

Validated

SDG: 200714-71
Location: TATA - I H

Client Reference: D20210
Order Number: 1286

Report Number: 559905
Superseded Report:

Test Completion Dates

Lab Sample No(s)	22471874	22471875
Customer Sample Ref.	BH1	BH1
AGS Ref.		
Depth	3.00 - 3.45	1.00 - 2.00
Type	Soil/Solid (S)	Soil/Solid (S)
Alkali Metals by iCap-OES (Soil)	21-Jul-2020	21-Jul-2020
Asbestos ID in Solid Samples	20-Jul-2020	20-Jul-2020
EPH CWG GC (S)	20-Jul-2020	20-Jul-2020
GRO by GC-FID (S)	17-Jul-2020	17-Jul-2020
Metals in solid samples by OES	21-Jul-2020	21-Jul-2020
PAH by GCMS	21-Jul-2020	21-Jul-2020
pH	17-Jul-2020	17-Jul-2020
Sample description	16-Jul-2020	16-Jul-2020
Total Organic Carbon	21-Jul-2020	21-Jul-2020
TPH CWG GC (S)	20-Jul-2020	20-Jul-2020
VOC MS (S)	17-Jul-2020	17-Jul-2020



CERTIFICATE OF ANALYSIS

SDG:	200714-71	Client Reference:	D20210	Report Number:	559905
Location:	TATA - I H	Order Number:	1286	Superseded Report:	

Appendix

1. Results are expressed on a dry weight basis (dried at 35°C) for all soil analyses except for the following: NRA and CEN Leach tests, flash point LOI, pH, ammonium as NH₄ by the BRE method, VOC TICs and SVOC TICs.

2. If sufficient sample is received a sub sample will be retained free of charge for 30 days after analysis is completed (e-mailed) for all sample types unless the sample is destroyed on testing. The prepared soil sub sample that is analysed for asbestos will be retained for a period of 6 months after the analysis date. All bulk samples will be retained for a period of 6 months after the analysis date. All samples received and not scheduled will be disposed of one month after the date of receipt unless we are instructed to the contrary. Once the initial period has expired, a storage charge will be applied for each month or part thereof until the client cancels the request for sample storage. ALS reserve the right to charge for samples received and stored but not analysed.

3. With respect to turnaround, we will always endeavour to meet client requirements wherever possible, but turnaround times cannot be absolutely guaranteed due to so many variables beyond our control.

4. We take responsibility for any test performed by sub-contractors (marked with an asterisk). We endeavour to use UKAS/MCERTS Accredited Laboratories, who either complete a quality questionnaire or are audited by ourselves. For some determinands there are no UKAS/MCERTS Accredited Laboratories, in this instance a laboratory with a known track record will be utilised.

5. If no separate volatile sample is supplied by the client, or if a headspace or sediment is present in the volatile sample, the integrity of the data may be compromised. This will be flagged up as an invalid VOC on the test schedule and the result marked as deviating on the test certificate.

6. NDP - No determination possible due to insufficient/unsuitable sample.

7. Results relate only to the items tested.

8. LoDs (Limit of Detection) for wet tests reported on a dry weight basis are not corrected for moisture content.

9. **Surrogate recoveries** - Surrogates are added to your sample to monitor recovery of the test requested. A % recovery is reported, results are not corrected for the recovery measured. Typical recoveries for organics tests are 70-130%. Recoveries in soils are affected by organic rich or clay rich matrices. Waters can be affected by remediation fluids or high amounts of sediment. Test results are only ever reported if all of the associated quality checks pass; it is assumed that all recoveries outside of the values above are due to matrix affect.

10. Stones/debris are not routinely removed. We always endeavour to take a representative sub sample from the received sample.

11. In certain circumstances the method detection limit may be elevated due to the sample being outside the calibration range. Other factors that may contribute to this include possible interferences. In both cases the sample would be diluted which would cause the method detection limit to be raised.

12. Mercury results quoted on soils will not include volatile mercury as the analysis is performed on a dried and crushed sample.

13. For leachate preparations other than Zero Headspace Extraction (ZHE) volatile loss may occur.

14. For the BSEN 12457-3 two batch process to allow the cumulative release to be calculated, the volume of the leachate produced is measured and filtered for all tests. We therefore cannot carry out any unfiltered analysis. The tests affected include volatiles GCFID/GCMS and all subcontracted analysis.

15. Analysis and identification of specific compounds using GCFID is by retention time only, and we routinely calibrate and quantify for benzene, toluene, ethylbenzenes and xylenes (BTEX). For total volatiles in the C5-C12 range, the total area of the chromatogram is integrated and expressed as ug/kg or ug/l. Although this analysis is commonly used for the quantification of gasoline range organics (GRO), the system will also detect other compounds such as chlorinated solvents, and this may lead to a falsely high result with respect to hydrocarbons only. It is not possible to specifically identify these non-hydrocarbons, as standards are not routinely run for any other compounds, and for more definitive identification, volatiles by GCMS should be utilised.

16. We are accredited to MCERTS for sand, clay and loam/topsoil, or any of these materials - whether these are derived from naturally occurring soil profiles, or from fill/made ground, as long as these materials constitute the major part of the sample. Other coarse granular material such as concrete, gravel and brick are not accredited if they comprise the major part of the sample.

General

17. **Tentatively Identified Compounds (TICs)** are non-target peaks in VOC and SVOC analysis. All non-target peaks detected with a concentration above the LoD are subjected to a mass spectral library search. Non-target peaks with a library search confidence of >75% are reported based on the best mass spectral library match. When a non-target peak with a library search confidence of <75% is detected it is reported as "mixed hydrocarbons". Non-target compounds identified from the scan data are semi-quantified relative to one of the deuterated internal standards, under the same chromatographic conditions as the target compounds. This result is reported as a semi-quantitative value and reported as Tentatively Identified Compounds (TICs). TICs are outside the scope of UKAS accreditation and are not moisture corrected.

18. Sample Deviations

If a sample is classed as deviated then the associated results may be compromised.

1	Container with Headspace provided for volatiles analysis
2	Incorrect container received
3	Deviation from method
§	Sampled on date not provided
◆	Sample holding time exceeded in laboratory
@	Sample holding time exceeded due to late arrival of instructions or samples

19. Asbestos

When requested, the individual sub sample scheduled will be analysed in house for the presence of asbestos fibres and asbestos containing material by our documented in house method TM048 based on HSG 248 (2005), which is accredited to ISO17025. If a specific asbestos fibre type is not found this will be reported as "Not detected". If no asbestos fibre types are found all will be reported as "Not detected" and the sub sample analysed deemed to be clear of asbestos. If an asbestos fibre type is found it will be reported as detected (for each fibre type found). Testing can be carried out on asbestos positive samples, but, due to Health and Safety considerations, may be replaced by alternative tests or reported as No Determination Possible (NDP). The quantity of

Identification of Asbestos in Bulk Materials & Soils

The results for identification of asbestos in bulk materials are obtained from supplied bulk materials which have been examined to determine the presence of asbestos fibres using ALS (Hawarden) in-house method of transmitted/polarised light microscopy and central stop dispersion staining, based on HSG 248 (2005).

The results for identification of asbestos in soils are obtained from a homogenised sub sample which has been examined to determine the presence of asbestos fibres using ALS (Hawarden) in-house method of transmitted/polarised light microscopy and central stop dispersion staining, based on HSG 248 (2005).

Asbestos Type	Common Name
Chrysotile	White Asbestos
Amosite	Brown Asbestos
Crocidolite	Blue Asbestos
Fibrous Actinolite	-
Fibrous Anthophyllite	-
Fibrous Tremolite	-

Visual Estimation Of Fibre Content

Estimation of fibre content is not permitted as part of our UKAS accredited test other than: - Trace - Where only one or two asbestos fibres were identified.

Respirable Fibres

Respirable fibres are defined as fibres of <3 µm diameter, longer than 5 µm and with aspect ratios of at least 3:1 that can be inhaled into the lower regions of the lung and are generally acknowledged to be most important predictor of hazard and risk for cancers of the lung.
Standing Committee of Analysts, *The Quantification of Asbestos in Soil* (2017).

Further guidance on typical asbestos fibre content of manufactured products can be found in HSG 264.

The identification of asbestos containing materials and soils falls within our schedule of tests for which we hold UKAS accreditation, however opinions, interpretations and all other information contained in the report are outside the scope of UKAS accreditation.