

Title: Church Street Development	Job No. 14657	Drawing No. 510	Revision. B	15.06.2022	Prepared by RGP
---	-------------------------	---------------------------	-----------------------	-------------------	---------------------------

Cover Type	Manufacturer	Product Name	Manufacturers Ref:	Clear Opening(mm)	Frame size (mm)	Seal	Material	Loading	Notes:
<i>B1</i>	<i>Saint_Gobain</i>	Valiant	<i>BM061</i>	<i>600x600</i>	<i>752x752x75</i>	<i>Single</i>	<i>Ductile Iron</i>	<i>B125</i>	
<i>D1</i>	<i>Saint_Gobain</i>	Pam Inter AX	<i>BE030</i>	<i>675X675</i>	<i>875x875x150</i>	<i>Single</i>	<i>Ductile Iron</i>	<i>D400</i>	
<i>K1</i>	<i>Wade</i>	K5501 Super Seal Access Cover	K5501	152mm dia.		Double	<i>Nickle Bronze</i>		

Loading Class	Test Load Tonnes	NOTES
A15	1.5	Suitable for ares which can only be used by pedestrians and pedal cyclists
B125	12.5	Suitable for ares where slow moving delivery vans and public vehicles may have access
D400	40	Suitable for Carriageways, hard shoulders and parking areas for all types of fast moving vehicles



29 Bocam Park
Pencoed
Bridgend
CF35 5LJ

Job Title:
Glynneath, Neath,
Port Talbot

Job No. **14657**
Drwg No. **510**
Rev: **B**

Date: **15.06.22**
Prepared by: **RGP**

MH. REF	Cover Level	Invert Level	Depth (M)	Inc No.	Dia.	Invert	Out No.	Dia.	Invert	Eastings (M)	Northings (M)	Manhole size (mm)	Manhole Type	Cover Type	Notes:
F1-1	48.300	47.850	0.450	0	100	47.850	1	100	47.850			225	Type 4	B125	Private
F1-2	48.300	47.500	0.800	2	100	47.500	1	100	47.500			225	Type 4	B125	Private
F1-3	48.250	47.425	0.825	1	100	47.425	1	100	47.425			600	Type 3	B125	Adoptable
F2-1	47.850	47.400	0.450	0	100	47.400	1	100	47.400			225	Type 4	B125	Private
F2-2	47.850	47.050	0.800	2	100	47.050	1	100	47.050			225	Type 4	B125	Private
F3-1	47.850	47.400	0.450	0	100	47.400	1	100	47.400			225	Type 4	B125	Private
F3-2	47.850	47.050	0.800	2	100	47.050	1	100	47.050			225	Type 4	B125	Private
F4-1	47.850	47.400	0.450	0	100	47.400	1	100	47.400			225	Type 4	B125	Private
F4-2	47.850	47.050	0.800	2	100	47.050	1	100	47.050			225	Type 4	B125	Private
F5-1	47.400	46.950	0.450	0	100	46.950	1	100	46.950			225	Type 4	B125	Private
F5-2	47.400	46.600	0.800	2	100	46.600	1	100	46.600			2225	Type 4	B125	Private
F5-3	47.600	46.800	0.800	2	100	46.800	1	100	46.800			600	Type 3	D400	Adoptable
F6-1	47.400	46.950	0.450	0	100	46.950	1	100	46.950			225	Type 4	B125	Private
F6-2	47.400	46.600	0.800	2	100	46.600	1	100	46.600			225	Type 4	B125	Private
F7-1	47.400	46.950	0.450	0	100	46.950	1	100	46.950			225	Type 4	B125	Private
F7-2	47.400	46.600	0.800	2	100	46.600	1	100	46.600			225	Type 4	B125	Private
F8-1	47.400	46.950	0.450	0	100	46.950	1	100	46.950			225	Type 4	B125	Private
F8-2	47.400	46.600	0.800	2	100	46.600	1	100	46.600			225	Type 4	B125	Private
F9-1	47.400	46.950	0.450	0	100	46.950	1	100	46.950			225	Type 4	B125	Private
F9-2	47.400	46.600	0.800	3	100	46.600	1	100	46.600			600	Type 3	B125	Adoptable
F10-1	47.400	46.950	0.450	0	100	46.950	1	100	46.950			225	Type 4	B125	Private
F10-2	47.400	46.600	0.800	2	100	46.600	1	100	46.600			600	Type 3	D400	Private
F10-3	47.400	46.350	1.050	1	100	46.350	1	100	46.350			600	Type 3	D400	Adoptable
EF1	46.760	45.700	1.060	1 2	100 150	45.700	1	100	45.700			Exist		D400	Existing MH

*Note: - Co-ordinates are for Guidance only and relationship to building/Landscaping/Kerbing etc should be checked by contractor prior to construction

Bold = Revision

 Vale Consultancy		29 Bocam Park Pencoed Bridgend CF35 5LJ		Job Title: Glynneath, Neath, Port Talbot		Job No. 14657 Drwg No. 510 Rev: B		Date: 15.06.21 Prepared by: RGP							
MH. REF	Cover Level	Invert Level	Depth (M)	Inc No.	Dia.	Invert	Out No.	Dia.	Invert	Eastings (M)	Northings (M)	Manhole size (mm)	Manhole Type	Cover Type	Notes:
RE1-1	48.300	47.950	0.350		150								Rodding Eye	A15	Private
IC1-2	48.300	47.400	0.900	1	150	47.400	1	150	47.400			200	Type 4	D400	Private
S1-3	48.300	47.350	0.950	1	150	47.350	1	100	47.350			600	Type 3	D400	Private Flow Control
S1-4	48.300	47.300	1.000	1	150	47.300	1	100	47.300			250	Type 3	D400	Adoptable
RE2-1	47.850	47.500	0.350		150								Rodding Eye	A15	Private
IC2-2	47.850	46.950	0.900	1	150	46.950	1	150	46.950			200	Type 4	D400	Private
S2-3	47.850	46.900	0.950	1	150	46.900	1	100	46.900			600	Type 4	B125	Private Flow Control
RE3-1	47.850	47.500	0.350		150								Rodding Eye	A15	Private
IC3-2	47.850	46.950	0.900	1	150	46.950	1	150	46.950			200	Type 4	D400	Private
S3-3	47.850	46.900	0.950	1	150	46.900	1	100	46.900			600	Type 3	D400	Private Flow Control
RE4-1	47.850	47.500	0.350		150								Rodding Eye	A15	Private
IC4-2	47.850	46.950	0.900	1	150	46.950	1	150	46.950			200	Type 4	D400	Private
S4-3	47.850	46.900	0.950	1	150	46.900	1	100	46.900			600	Type 3	D400	Private Flow Control
RE5-1	47.400	47.050	0.350		150								Rodding Eye	A15	Private
IC5-2	47.400	46.500	0.900	1	150	46.500	1	150	46.500			200	Type 4	B125	Private
S5-3	47.400	46.450	0.950	1	150	46.450	1	100	46.450			600	Type 3	D400	Private Flow Control
RE6-1	47.400	47.050	0.350		150								Rodding Eye	A15	Private
IC6-2	47.400	46.500	0.900	1	150	46.500	1	150	46.500			200	Type 4	D400	Private
S6-3	47.250	46.450	0.800	1	150	46.450	1	100	46.450			600	Type 3	D400	Private Flow Control
RE7-1	47.400	47.050	0.350		150								Rodding Eye	A15	Private
IC7-2	47.400	46.500	0.900	1	150	46.500	1	150	46.500			200	Type 4	D400	Private
S7-3	47.250	46.450	0.800	1	150	46.450	1	100	46.450			600	Type 3	D400	Private Flow Control
RE8-1	47.400	47.050	0.350		150								Rodding Eye	A15	Private
IC8-2	47.400	46.500	0.900	1	150	46.500	1	150	46.500			200	Type 4	D400	Private
S8-3	47.250	46.450	0.800	1	150	46.450	1	100	46.450			600	Type 3	D400	Private Flow Control
RE9-1	47.400	47.050	0.350		150								Rodding Eye	A15	Private
IC9-2	47.400	46.500	0.900	1	150	46.500	1	150	46.500			200	Type 4	D400	Private
S9-3	47.350	46.450	0.900	1	150	46.450	1	100	46.450			600	Type 3	D400	Private Flow Control
RE10-1	47.400	46.900	0.500	1	150								Rodding Eye	A15	Private
S10-2	47.400	46.500	0.900	1	150	46.500	1	150	46.500			600	Type 4	B125	Private
S10-3	47.350	46.400	0.950	1	150	46.400	1	100	46.400			600	Type 3	D400	Private Flow Control
S10-4	47.400	46.175	1.225	2	100	46.175	1	150	46.175			1200	Type 2	D400	Adoptable

*Note: - Co-ordinates are for Guidance only and relationship to building/Landscaping/Kerbing etc should be checked by contractor prior to construction

Bold = Revision