

| Unit Ref | Roadname        | Column Height      | Column Manufacturer | Column Model Number/Order Code | Lantern Mounting | Lantern Tilt | Door Lock                                                                | Planting Depth     | Lantern Manufacturer/Model | Colour Temperature | No. of LEDs | Lantern Shield Kit | RAL Colour | Lantern Code | Drive Current | Lantern Guarantee Period | LED Driver       | NEMA Socket | Central Management System CMS                      | Dimming Time    | Dim to Light Output | Double Pole Isolator                                                                     | Fuse               | Lantern to Isolator Cabling                                                    | Paint Specification | Column Paint Colour | Electrical Service Type    | Highway/Private Ownership | Maintenance Company Details (If not to be adopted) | Column Setback Requirements |
|----------|-----------------|--------------------|---------------------|--------------------------------|------------------|--------------|--------------------------------------------------------------------------|--------------------|----------------------------|--------------------|-------------|--------------------|------------|--------------|---------------|--------------------------|------------------|-------------|----------------------------------------------------|-----------------|---------------------|------------------------------------------------------------------------------------------|--------------------|--------------------------------------------------------------------------------|---------------------|---------------------|----------------------------|---------------------------|----------------------------------------------------|-----------------------------|
| LC1      | Harvey Crescent | 6m                 | CU Phosco           | FR2506T01 EN40                 | Post Top         | 0 Degrees    | Flush Door with double lock - 8mm Allen bolt with anti vandal centre pin | 1.0m               | Urbis Axia 3.1             | 3000K              | 8           | N                  | RAL70 40   | 5266         | 600mA         | 12 Years                 | Philips Xitanium | 7 Pin       | Telensa 5 Pin - GPS Enabled Product Code T2E1N-G-3 | 00:00 - 05:30am | 30%                 | Lucy Trojan Midi THM0014962, complete with 6mm² brown & blue tails, plus 6mm² earth lead | 6A - BS88 MD Fuse  | 7.25m of 3 core 1.5mm² circular flex H05VV-F temperature range -15°C to + 70°C | Galv Finish         | Galv Finish         | Direct DNO (National Grid) | Highway                   | N/A                                                | Back of Footpath            |
| Ex1      | Harvey Crescent | Existing to remain | Existing to remain  | Existing to remain             | Side Entry       | 0 Degrees    | Existing to remain                                                       | Existing to remain | Urbis Axia 3.1             | 3000K              | 8           | N                  | RAL70 40   | 5266         | 600mA         | 12 Years                 | Philips Xitanium | 7 Pin       | Telensa 5 Pin - GPS Enabled Product Code T2E1N-G-3 | 00:00 - 05:30am | 30%                 | Existing to remain                                                                       | Existing to remain | 7.25m of 3 core 1.5mm² circular flex H05VV-F temperature range -15°C to + 70°C | Existing to remain  | Existing to remain  | Existing to remain         | Highway                   | N/A                                                | Back of Footpath            |
| Ex2      | Harvey Crescent | Existing to remain | Existing to remain  | Existing to remain             | Side Entry       | 0 Degrees    | Existing to remain                                                       | Existing to remain | Urbis Axia 3.1             | 3000K              | 8           | N                  | RAL70 40   | 5266         | 600mA         | 12 Years                 | Philips Xitanium | 7 Pin       | Telensa 5 Pin - GPS Enabled Product Code T2E1N-G-3 | 00:00 - 05:30am | 30%                 | Existing to remain                                                                       | Existing to remain | 7.25m of 3 core 1.5mm² circular flex H05VV-F temperature range -15°C to + 70°C | Existing to remain  | Existing to remain  | Existing to remain         | Highway                   | N/A                                                | Back of Footpath            |
| Ex3      | Harvey Crescent | Existing to remain | Existing to remain  | Existing to remain             | Side Entry       | 0 Degrees    | Existing to remain                                                       | Existing to remain | Urbis Axia 3.1             | 3000K              | 8           | N                  | RAL70 40   | 5266         | 600mA         | 12 Years                 | Philips Xitanium | 7 Pin       | Telensa 5 Pin - GPS Enabled Product Code T2E1N-G-3 | 00:00 - 05:30am | 30%                 | Existing to remain                                                                       | Existing to remain | 7.25m of 3 core 1.5mm² circular flex H05VV-F temperature range -15°C to + 70°C | Existing to remain  | Existing to remain  | Existing to remain         | Highway                   | N/A                                                | Back of Footpath            |