

Heating

Product Information

QUHZ-W40VA / EHPT20Q-VM2EA

Ecodan Monobloc 4kW Air Source Heat Pump
With Thermal Store

Making a
World of
Difference



Our new 4kW monobloc Ecodan heat pump system combines market leading efficiency in hot water production with reliable and renewable heat provision all year round.

The Ecodan QUHZ is the ideal solution for new build homes where strict building regulations drive down the space heating demand, making the production of hot water the dominant load.

The Ecodan QUHZ operates with a market leading low noise output and built in energy monitoring as standard. The thermal store has been specifically designed to work with this system, giving high hot water output without the need to pasteurise the water.

Key Features

- High efficiency hot water heating performance
- Class leading low noise operation
- Energy monitoring as standard
- No stored water, no risk of legionella
- High hot water capacity for larger dwellings
- Pre-plumbed and wired for faster installation
- Compatible with Mitsubishi Electric wireless room controllers
- Wi-Fi control available

Application Examples


- New Build UK homes
- Cafes and Restaurants
- Dental / Doctor's Surgeries



Certificate Number: MCS HP0002
Product Type: Heat Pumps
Product Reference: QUHZ-W40VA



Air Conditioning | Heating
Ventilation | Controls



ecodan[®]
Renewable Heating Technology

OUTDOOR UNIT		QUHZ-W40VA	THERMAL STORE		EHPT20Q-VM2EA
HEAT PUMP COMBINATION HEATER - 55°C	ErP Rating	A+	NOMINAL THERMAL STORE WATER VOLUME (LITRES)		200
	η_{Ls}	117%	WATER TEMPERATURE RANGE	DHW Mode (°C)	40-70°C
	SCOP	2.90		Space Heating Mode (°C)	25-60°C
HEAT PUMP COMBINATION HEATER - Large Profile ¹	ErP Rating	A	MECHANICAL ZONES		DHW and 1 Heating Zone (2 Zone capability with 3rd party 2-port valves)
	η_{wh}	129%	OPERATING AMBIENT TEMPERATURE (°C DB)		0 ~ +35°C (RH<80%)
	COP	3.00	SOUND PRESSURE LEVEL AT 1M (dBA)		30
HEATING ² (A-3/W55)	Capacity (kW)	4.32	SOUND POWER LEVEL (dBA) ⁴		40
	Power Input (kW)	2.18	STANDING HEAT LOSS (kWh/24hours)		1.63
	COP	1.98	WATER DATA	Primary Pump	Grundfos Solar PML 25-145 180
OPERATING AMBIENT TEMPERATURE (°C DB)		-15 ~ +35°C		Sanitary Hot Water Pump	Grundfos Solar PML 25-145 180
SOUND PRESSURE LEVEL AT 1M (dBA) ³		43		Connection Size (mm) Heating / DHW	22 / 22
SOUND POWER LEVEL (dBA) ⁴		53		Primary Expansion Vessel (Litres)	18
WATER DATA	Pipework Size (mm)	15		Charge Pressure (MPa (Bar))	0.1 (1)
	Flow Rate (l/min)	3 to 8	WATER SAFETY DEVICES	Pressure relief valve (Mpa (Bar))	0.3 (3) - 2 No. devices
DISTANCE BETWEEN OUTDOOR UNIT AND THERMAL STORE (M) DIMENSIONS (mm)	Height Difference	5		Flow sensor (supplied)	Min. flow 1.3 L/min
	Piping Length	15		Manual reset thermostat	85°C
DIMENSIONS	Width	809+70 ⁵	DIMENSIONS (mm)	Width	595
	Depth	300+20 ⁵		Depth	680
	Height	715		Height	1600
WEIGHT (kg)		57		WEIGHT EMPTY / FULL (kg)	77 / 283
ELECTRICAL DATA		Powered from indoor unit	ELECTRICAL DATA	Electrical Supply	220-240v, 50Hz
				Phase	Single
				Maximum Running Current (A)	15
				Fuse Rating - MCB Sizes (A) ⁶	20
			OPTIONAL SIMPLIFIED WIRELESS ROOM THERMOSTAT AND WIRELESS RECEIVER		PAR-WT50-E Controller and PAR-WR51-E Receiver

¹ Combination with EHPT20Q-VM2EA Thermal Store.

² Under normal heating conditions at outdoor temp: -3°CDB / -4°CWB, outlet water temp 55°C, inlet water temp 47°C.

³ Under normal heating conditions at outdoor temp: 7°CDB / 6°CWB, outlet water temp 55°C, inlet water temp 47°C as tested to BS EN14511.

⁴ Sound power level tested to BS EN12102.

⁵ Grille or pipe cover.


⁶ MCB Sizes BS EN60898-2 & BS EN60947-2.

η_{Ls} is the seasonal space heating energy efficiency (SSHEE)


η_{wh} is the water heating energy efficiency

DIMENSIONS

QUHZ-W40VA



EHPT20Q-VM2EA



Telephone: 01707 282880

email: heating@meuk.mee.com web: heating.mitsubishielectric.co.uk

UNITED KINGDOM Mitsubishi Electric Europe Living Environmental Systems Division
Travellers Lane, Hatfield, Hertfordshire, AL10 8XB, England General Enquiries Telephone: 01707 282880 Fax: 01707 278881

IRELAND Mitsubishi Electric Europe Westgate Business Park, Ballymount, Dublin 24, Ireland
Telephone: Dublin (01) 419 8800 Fax: Dublin (01) 419 8890 International code: (003531)

Country of origin: United Kingdom - Japan - Thailand - Malaysia. ©Mitsubishi Electric Europe 2015. Mitsubishi and Mitsubishi Electric are trademarks of Mitsubishi Electric Europe B.V. The company reserves the right to make any variation in technical specification to the equipment described, or to withdraw or replace products without prior notification or public announcement. Mitsubishi Electric is constantly developing and improving its products. All descriptions, illustrations, drawings and specifications in this publication present only general particulars and shall not form part of any contract. All goods are supplied subject to the Company's General Conditions of Sale, a copy of which is available on request. Third-party product and brand names may be trademarks or registered trademarks of their respective owners.



Printed on November 2015 SAP No. 291279



www.greengateway.mitsubishielectric.co.uk

Mitsubishi Electric UK's commitment
to the environment

Follow us @meuk_ies
Follow us @green_gateway

Mitsubishi Electric
Living Environmental Systems UK

youtube.com/mitsubishielectric2