

rubberized roof covering, or similar approved, laid in accordance with manufacturers recommendations at 15mm external quality plywood boarding at 5mm wood fixings laid to falls at 200x50mm c24 joists @ 400mm centres

Kooltherm K107 Kingspan insulation laid between joists (150mm)
Kooltherm K118 Kingspan (52.5mm) below joists to achieve a U-value of 0.13 W/m²K

25mm min. continuous eaves ventilation to comply with Part F2, Building Regulations

roof covering dressed under tiles

4uo. 150x100mm r.c. lintels built over door openings

12.5mm foil backed plaster board with skim finish

19mm tag weyrooc boarding at 175x50mm c24 joists @ 400mm centres

100mm glass wool insulation laid to floor void to prevent sound passage above 40 decibels

dpc
wall to be built up to new floor level

existing foundations to be exposed checked by S/C or I prior to commencement

floor to floor to match existing

SECTION A-A

Fine Line		Client	
Architectural Services Ltd.		Ms Sarah Hotson	
30 Pond Mawr Garth Maesteg Bridgend CF34 0SX		Project 17 Cefn Gelli, Cwmgwrach, Neath.	
Tel: 01656 732042 Email: fineline248@googlemail.com		Drawing Title Section A-A.	
Date August 2024	Scale 1:50.	Drawing No. 17CefnGelli/WD/06.	