

**SETTING OUT:**  
ALL DIMENSIONS ARE TAKEN FROM  
BRICKWORK/BLOCKWORK FACE AND PLASTERBOARD  
FACE OF STUD PARTITIONS.

**LINTELS:**  
REFER TO MANUFACTURER'S SCHEDULE FOR  
REFERENCES AND SIZES.

PROVIDE CAVITY TRAYS OVER ALL LINTELS. TRAY TO EXTEND 300mm EACH SIDE OF OPENING WITH A 15mm PROJECTION TO THE FRONT OF THE LINTEL.

WEEPHOLES TO BE PROVIDED TO BRICKWORK OVER  
LINTELS @ 450c/c MAX IN EXTERNAL OPENINGS.

**INSULATION**  
REFER TO INSULATION SCHEDULE FOR WALL, LOFT AND  
FLOOR SLAB INSULATION MATERIAL AND THICKNESS  
ETC.

**ENTRANCE DOOR FEATURES:**  
FOR DOOR SURROUND AND CANOPY DETAILS REFER  
STD. DETAILS.

**GAS PROTECTION:**  
IF GAS PROTECTION IS REQUIRED, REFER TO  
STANDARD DETAILS.

**GENERAL:**  
CONSTRUCTION PACK TO BE READ IN CONJUNCTION  
WITH GENERAL SPECIFICATION AND STANDARD  
DETAILS.

